



EH 30 Model – 1/4" NPT Pipe Size (Normally Closed) Model Number Breakdown

Start with your Port Diameter	(Clark Cooper base model number)		Next, choose your Voltage / Hz	(Add the following to the model number)		Add any OPTIONAL Extras	(Add the following to the model number)
Larger port = more flow Smaller port = higher differential pressure 0.019"	(EH30-041-)	→	24/60	(A024)	+	Din Connector (Not Explosion Proof) [Adaptor for quick electrical connection to the coil]	(DN)
			120/60	(A120)		General Service (Not Explosion Proof) [Can be used in non-hazardous locations]	(GS)
			240/60	(A240)		Hydrogen Service (Helium Leak Test) [Class 5 Leakage test with Helium]	(HY)
0.032"	(EH30-042-)	→	12/DC	(D012)	+	Normally Open	(NO)
			24/DC	(D024)		Oxygen Clean [Special cleaning with black light testing]	(OX)
			120/DC	(D120)		Cryogenic Service [Design modification and special cleaning]	(CY)
						Tube Connector [Flared adaptor to directly connect high pressure tubing]	(TC)
						Class 5 Leakage Testing [Leakage testing using Air as per FCI 91-2-2004]	(T5)

Example Model Number: **EH30-042-XXXX-XX**

If extras are added, the price increases (or decreases) as indicated above.