



EH 40 Model (Normally Closed) Price Chart

Start with your Port Diameter	(Clark Cooper base model number)	Next, choose your Voltage / Hz	(Add the following to the model number)
1/4" Cv = 1.1 Max ΔP up to AC 7,500 psi (10,000 optional) DC 3,500 psi (5,000 optional)	(EH40-04-)	24/60	(A024)
		120/60	(A120)
		240/60	(A240)
1/2" Cv = 4.5 Max ΔP up to AC 7,500 psi (10,000 optional) DC 3,600 psi (7,200 optional)	(EH40-08-)	12/DC	(D012)
		24/DC	(D024)
		120/DC	(D120)

+

Add any OPTIONAL Extras	(Add the following to the model number)
Din Connector (Not Explosion Proof) [Adaptor that allows quick electrical connection to the coil]	(DN)
General Service (Not Explosion Proof) [Can be used in non-hazardous locations]	(GS)
Hydrogen Service (Helium Leak Test) [Material modification and Class 5 testing with Helium]	(HY)
Normally Open	(NO)
Oxygen Clean [Special cleaning with black light testing]	(OX)
1/4" Straight Thread [-4 J1926 connection that utilizes an O-ring for easy sealing]	(S4)
1/2" Straight Thread [-8 J1926 connection that utilizes an O-ring for easy sealing]	(S8)
Tube Connector [Flared adaptor to directly connect high pressure tubing]	(TC)
Viton O-rings [Higher temperature and chemical resistance]	(VT)
Higher Pressure (22 Watt Coil) [See chart on EH40 catalog page for more information]	(XP)
Class 5 Leakage Testing [Leakage testing with Air as per FCI 91-2-2004]	(T5)

Example Model Number: **EH40-XX-XXXX-XX**

**If extras are added, the price increases
(or decreases) as indicated above.**