



## EH 50 Model – 1/2" NPT Pipe Size (Normally Closed) Model Number Breakdown

Start with your Port Diameter	(Clark Cooper base model number)	Next, choose your Voltage / Hz	(Add the following to the model number)
Full Port	(EH50-08-)	24/60	( A024 )
		120/60	( A120 )
		240/60	( A240 )
		12/DC	( D012 )
		24/DC	( D024 )
		120/DC	( D120 )

+

Add any OPTIONAL Extras	(Add the following to the model number)
Integrated Check Valve [Protect against back pressure]	( CK )
Din Connector (Not Explosion Proof) [Adaptor that allows quick electrical connection to the coil]	( DN )
General Service (Not Explosion Proof) [Can be used in non-hazardous locations]	( GS )
Hydrogen Service (Helium Leak Test) [Class 5 Leakage test with Helium]	( HY )
Normally Open [AC Only]	( NO )
Oxygen Clean [Special cleaning with black light testing ]	( OX )
316 Stainless Steel Valve Body	( SS )
Tube Connector [Flared adaptor to directly connect high pressure tubing]	( TC )
Viton O-rings [Higher temperature and chemical resistance]	( VT )
Higher Pressure (22 Watt Coil) [Max. Pressure Increased to 10,000 psi (AC) OR 5,000 psi (DC)]	( XP )
Class 5 Leakage Testing [Leakage Testing using Air as per FCI 91-2-2004]	( T5 )

**Example Model Number: EH50-08-XXXX-XX**

**If extras are added, the price increases (or decreases) as indicated above.**