



EH 40 Model (Normally Closed) Model Number Breakdown

Start with your Port Diameter	(Clark Cooper base model number)		Next, choose your Voltage / Hz	(Add the following to the model number)		Add any OPTIONAL Extras	(Add the following to the model number)
1/4"	(EH40-04-)	→	24/60	(A024)	+	Din Connector (Not Explosion Proof) [Adaptor that allows quick electrical connection to the coil]	(DN)
			120/60	(A120)		General Service (Not Explosion Proof) [Can be used in non-hazardous locations]	(GS)
			240/60	(A240)		Hydrogen Service (Helium Leak Test) [Material modification and Class 5 testing with Helium]	(HY)
1/2"	(EH40-08-)	→	12/DC	(D012)	+	Normally Open	(NO)
			24/DC	(D024)		Oxygen Clean [Special cleaning with black light testing]	(OX)
			120/DC	(D120)		1/4" Straight Thread [-4 J1926 connection that utilizes an O-ring for easy sealing]	(S4)
						1/2" Straight Thread [-8 J1926 connection that utilizes an O-ring for easy sealing]	(S8)
						Tube Connector [Flared adaptor to directly connect high pressure tubing]	(TC)
						Viton O-rings [Higher temperature and chemical resistance]	(VT)
						Higher Pressure (22 Watt Coil) [See chart on EH40 catalog page for more information]	(XP)
						Class 5 Leakage Testing [Leakage testing with Air as per FCI 91-2-2004]	(T5)

Example Model Number: **EH40-XX-XXXX-XX**

**If extras are added, the price increases
(or decreases) as indicated above.**

Service data including fluid or gas type and maximum pressure are required at the time of order.
Please note all configurations may not be possible.