



EH 50 Model – 1/2" NPT Pipe Size (Normally Closed) Model Number Breakdown

Start with your Port Diameter	(Clark Cooper base model number)	Next, choose your Voltage / Hz	(Add the following to the model number)	Add any OPTIONAL Extras	(Add the following to the model number)
Full Port	(EH50-08-)	24/60	(A024)	Integrated Check Valve [Protect against back pressure]	(CK)
		120/60	(A120)	Din Connector (Not Explosion Proof) [Adaptor that allows quick electrical connection to the coil]	(DN)
		240/60	(A240)	General Service (Not Explosion Proof) [Can be used in non-hazardous locations]	(GS)
		12/DC	(D012)	Hydrogen Service (Helium Leak Test) [Class 5 Leakage test with Helium]	(HY)
		24/DC	(D024)	Normally Open [AC Only]	(NO)
		24/DC	(D024)	Oxygen Clean [Special cleaning with black light testing]	(OX)
		120/DC	(D120)	316 Stainless Steel Valve Body	(SS)
				Tube Connector [Flared adaptor to directly connect high pressure tubing]	(TC)
				Viton O-rings [Higher temperature and chemical resistance]	(VT)
				Higher Pressure (22 Watt Coil) [Max. Pressure Increased to 10,000 psi (AC) OR 5,000 psi (DC)]	(XP)
				Class 5 Leakage Testing [Leakage Testing using Air as per FCI 91-2-2004]	(T5)

Example Model Number: **EH50-08-XXXX-XX**

**If extras are added, the price increases
(or decreases) as indicated above.**