



EH70 Model (Normally Closed) Model Number Breakdown

Connection Size in NPT	CC #	Connection Type	CC #	Voltage	CC #	Fluid	CC #			
1/2"	(EH70-08)	NPT	(A-)	24/60	(A024-)	Gas	(G)	Add any OPTIONAL Extras		
3/4"	(EH70-12)	Socket Weld	(B-)	120/60	(A120-)			Cryogenic Service <small>[Design modification and special cleaning]</small>		(CY)
1"	(EH70-16)	150# Flange	(G-)	240/60	(A240-)	Liquid	(L)	Din Connector (Not Explosion Proof) <small>[Adaptor that allows quick electrical connection to the coil]</small>		(DN)
1 1/2"	(EH70-24)	300# Flange	(H-)	24/DC	(D024-)			ETL Listed Solenoid for Explosion Proof <small>(UL 1203, CSA/CAN C22.2 #30)</small>		(ETL)
2"	(EH70-32)	600# Flange	(J-)	120/DC	(D120-)	Liquid + Gas	(D)	Hydrogen Service (Helium Leak Test) <small>[Class 5 Leakage test using Helium]</small>		(HY)
				240/DC	(D240-)			Normally Open		(NO)
								Oxygen Clean <small>[Special cleaning with black light testing]</small>		(OX)
								Single Switch (General Service) <small>[Position indicating switch]</small>		(S1)
								Stainless Steel Tags <small>[Tag that identifies the valve]</small>		(SS)
								Single Switch (Explosion Proof) <small>[Position indicating switch]</small>		(X1)
								Class 5 Leakage Testing <small>[Leakage test using Air as per FCI 91-2-2004]</small>		(T5)
								ATEX/IECEX certified coil		(1A)
								Manual Override		(MN)

Example Model Number: EH70-24X-XXXX-X-XX