

## Listing Information

Document Issue: 2024.1

Title:	EXPLOSION-PROOF ENCLOSURES FOR USE IN CLASS I HAZARDOUS LOCATIONS
Company:	Clark Cooper
Product Information:	<p>10 Series Solenoids, Clark Cooper, Model Nos. 358017; followed by 0, 1, or 2; followed by 0, 1, 2, 3, 4, 5, 7, 8, or 9; followed by NXX.          All for use in: Class I Div 1 &amp; 2, Groups A, B, C, D; Class II, Div 1 &amp; 2, Groups E, F, &amp; G</p> <p>10 watt solenoid coils:          Temperature code T4: Ambient temperature range of -20 C to 65.6 C and maximum fluid temperature of 121.1 C</p> <p>22 watt solenoid coils:          Temperature code T3C: Ambient temperature range of -20 C to 50 C and maximum fluid temperature of 65.0 C</p>
Evaluated to the following:	A representative sample of the listed devices have been tested, investigated, and found to comply with the requirements of the Standard(s) for Explosion-Proof Enclosures for use in Class 1 Hazardous Locations (UL-1203 & CAN/CSA-C22.2 No. 30) and are identified with the cETL Listed Mark

Please refer to the *10 Series Solenoid Coil* manual for additional information.

This document contains a reproduction of the listing information in entirety found on the Intertek Directory of Listed Products. To receive this information directly from Intertek, please write to: [etlvalidations@intertek.com](mailto:etlvalidations@intertek.com)